



Model 1310 International Travelette® provides two roomy 3-man seats plus plenty of space in back for equipment. Ideal for railroad, utility and other work crews.

Modern, colorful interiors make driving a pleasure. In dark red, dark blue, sage or jet black. Three interior and three exterior trims to choose from—Standard, Deluxe or Custom.

1310/1510 Specifications

	1310	1510
GVW Range, Lbs., Standard	7,000	13,840
Optional	8,000, 9,000 or 10,000	15,000
Wheelbase, Inches, Standard	131, 134, 149,* 156	132, 156
Axle, Front	I Beam	I Beam
Capacity, Lbs.	3,800	4,000
Axle, Rear (New Improved)	Full Floating Hypoid	Full Floating Hypoid
Capacity, Lbs.	7,500	10,000—12,000
Ratios	4.30, 4.87	4.87, 5.57, 6.17
Brake Service	Self-Adjusting Hydraulic, Dual Operation Warning Light	
Size, Front	12 x 3"	14 x 2½"
Size, Rear	12 x 3"	14½ x 3" 15 x 4"***
Total Lining Area	294.6	333.0 407.3
Clutch, Standard	Single Plate Dry Disc 10½"	103.2 sq. in.
Optional	11-inch H.D. Diaphragm Type 11-inch Angle Link	
Electrical, Standard	12-Volt, 37 Amp. Alternator	12-Volt, 37 Amp. Alternator
Optional	50-Amp. Hr., 54-Plate Battery 61 Amp. Alternator 60 or 70 Amp. Hr. Battery	50-Amp. Hr., 54-Plate Battery 61 Amp. Alternator 60 or 70 Amp. Hr. Battery
Engine, Standard	6-258, 258 cu. in. 6-Cyl.	6-258, 258 cu. in. 6-Cyl.
Optional V-8	V-304, 304 cu. in. V-8 V-345, 345 cu. in. V-8 V-392, 392 cu. in. V-8	V-304, 304 cu. in. V-8 V-345, 345 cu. in. V-8 V-392, 392 cu. in. V-8
Fuel Tank, Standard	16 Gallon Mounted under Cab, Right Side	16 Gallon Mounted under Cab, Right Side
Optional	16 Gallon Mounted under Cab, Left Side	16 Gallon Mounted under Cab, Left Side
Suspension, Front	Leaf Spring	Leaf Spring
Capacity, Lbs.	3,100—3,500	4,000
Suspension, Rear	Leaf Spring	Leaf Spring
Capacity, Lbs.	5,000—7,500	10,000—12,000
Shock Absorbers, Standard	Front	Front and Rear
Optional	Rear	
Transmission, Standard	4-Speed, Fully-Synchronized	4-Speed, Fully-Synchronized
Optional	5-Speed, Direct or Overdrive 3-Speed Automatic	5-Speed, Direct or Overdrive
Tires, Standard	8.00 x 16.5 8-PR Front and Single Rear	7.50 x 17 8-PR Front and Dual Rear
Optional	8.00 x 16.5 10-PR Front and Single or Dual Rear 8.75 x 16.5 10-PR Front and Single Rear 9.50 x 16.5 8 & 10-PR Front and Single Rear 7.00 x 16 6-PR Front and Single or Dual Rear 7.50 x 16 6 & 8-PR Front and Single Rear	7.50 x 20 8-PR Front and Dual Rear
Wheels, Standard	5 Stud Steel Disc	5 Stud Steel Disc
Body, Standard	6½ ft. Bonus on Travelette Cab & Chassis	
Optional	9 ft. Regular 8 ft. Regular or Bonus	
Power Steering	Optional	Optional

*Use with Travelette Cab-
**12,000 Axles Only

Specifications, descriptions and illustrative material in this literature are as accurate as known at time of publication, but are subject to change without notice. Illustrations may include optional equipment and accessories and may not include all standard equipment.

The following trademarks of International Harvester Company are registered in the U.S. Patent Office: INTERNATIONAL, TRAVELETTE and 

 **INTERNATIONAL® TRUCKS**
INTERNATIONAL HARVESTER EXPORT COMPANY
CHICAGO, ILLINOIS, U. S. A.

Light/Heavy Hauler



International® Models 1310 and 1510